



SAFE RAPID ACCESS

Roofline System



- FLEXIBILITY TO QUICKLY CHANGE WORK LOCATIONS
- COST EFFECTIVE ALTERNATIVE TO SCAFFOLDING
- LONG-LIFE DURABILITY AND NON-CORROSIVE ALUMINUM
- LIGHTWEIGHT AND COMPACT FOR EASY STORAGE AND TRANSPORTATION

Roofline System

The patented **Roofline System** is one or more Easi-Dec platforms linked securely with our catwalk to form a continuous fully-guarded platform. The 26.4' Roofline System comprises of 2 Easi-Dec platforms and a catwalk and can be constructed in less than 30 minutes with no tools required. The use of the telescopic legs gives height adjustment in 1.2" increments and can even adjust to sloping ground. With a comprehensive range of accessories, the Roofline System offers numerous benefits and is ready to overcome all kinds of challenging access situations.

The Cushioned Rolling Window Bar provides a continuous platform support for load distribution. Particularly useful on vinyl siding, cedar shingles and exterior insulation.

While the standard leg height (10.9' - 18.2') is sold as part of the system, alternative leg lengths are also available.

TECHNICAL SPECIFICATION

Load rating	1000lb uniformly distributed
System weight	524lb
Platform size	6.6' x 2.6' wide
15' Catwalk Dimensions	2' x 15.2'
Material	6082T6 aluminum

COMPLIANCE

ANSI A10.8-2011
CSA Z271-10
CSA B354.5-07
CSA Z797-09
OH&S Act and Regulations for Construction Projects 213/91
OSHA S.1926.451
OSHA 1910.28

LEG SPECIFICATION

Standard legs	10.9' - 18.2' platform height
16' legs	9.9' - 15.7' platform height
14' legs	9' - 13.7' platform height
Short legs	7.7' - 9.6' platform height

Accessories

Catwalk: The lightweight aluminum staging is a standard 15.2' and is supplied with an integral handrail system and toe boards.

End Support Frame: Where restricted access precludes the use of the standard 6.6' Dec, a single leg support can be used. Designed to provide access where boundaries or projecting structures restrict normal platform use.

Stand-Off Kit: To enable access to or over deep soffits, the working platform can be fitted with a pair of 8" Stand-Off arms, enabling the platform to be positioned away from the building. Safe working is maintained by the addition of front handrails and toe boards.

Corner Kit: To enable access to large box-end gutters, or to provide a continuous working platform around corners, the addition of a Corner Kit provides stable support. The corner leg is attached to the platform and secured with the addition of an adjustable brace, enabling the platform to project beyond the end of the structure.

Note: Prior to use, a full onsite risk assessment must be carried out and in some circumstances, the Easi-Dec must be tied into the structure.



End Support Frame



Stand-Off Kit



Corner Kit



USA
Kee Safety, Inc.
100 Stradtman Street
Buffalo, NY 14206

Tel: (716) 896 4949
Fax: (716) 896 5696
Toll Free: (800) 851 5181

www.keesafety.com
Email: info@keesafety.com

Canada
Kee Safety, Ltd.
40 North Rivermede Rd., Units 6-7
Concord, Ontario L4K 2H3

Tel: (905) 669 1494
Fax: (905) 669 4347
Toll Free: (877) 505 5003

www.keesafety.ca
Email: info@keesafety.com